STUCCOMAX

StuccoMax is a high performance exterior finish that naturally bonds with exterior EPS foam used in both retro-fitting and new construction.

Comparison chart using StuccoMax vs EIFS or traditional three coat stucco.

	StuccoMax	EIFS	Stucco
Installation SF Per Man/HR	100	17	14
Contains Portland Cement	NO	YES	YES
Contains Acrylics and Known Carcinogens	NO	YES	YES
Likelihood of Cracking	LOW	LOW	HIGH
Adhesion to Foam	HIGH	HIGH	LOW
Impact Resistance	HIGH	LOW	MED
Total Installed & Painted Cost	\$4.00 / SF Avg.	\$6.00 / SF Avg.	\$6.00 / SF Avg.

Performance benefits at a glance-

- Provides a hard, durable single coat over EPS exterior walls, over 3500 PSI compressive strength
- Applies directly over EPS or CMU block
- Noncombustible building material
- Zero flame spread, and zero smoke developed indices
- Resistant to mold and mildew growth
- Single day application
- Impact and abrasion resistant
- Low shrinkage minimizing cracking
- Highly water resistant
- Resistant to freeze / thaw damage
- Highly resistant to sulphate attack
- Low permeability
- Hand or machine applied
- Direct application to EPS and other substrates
- Install StuccoMax with ambient temperatures above 45 degrees Fahrenheit.
- Silica free
- Qualifies for LEED points benefits